

**ADIX IX-DCKT970**



**CUT THE CORD THAT**

**BINDS YOU TO YOUR DESK**

**IWATSU**

**TOOLS THAT EVOLVE FASTER  
THAN YOUR BUSINESS**

- ▶▶▶ Is most of your time spent out of the office?
- ▶▶▶ Tired of missing important calls?
- ▶▶▶ Too many voice mail messages to return?

## Then the IX-DCKT970 is the solution you've been waiting for.

The IX-DCKT970 digital wireless key telephone emulates the functionality of a corded ADIX Omega-Phone, while enabling you with greater flexibility and improved productivity while away from your desk. From virtually any location in your office, IX-DCKT970 wireless capabilities allow you to answer important calls for increased efficiency and customer satisfaction. Iwatsu's IX-DCKT970 delivers the following advantages:

**Increased Mobility.** The IX-DCKT970 has seven times the range of a traditional wireless telephone.

**Digital Technology.** Provides voice clarity that is indistinguishable from a corded telephone.

**LCD Indication.** A 2-line/16-digit Liquid Crystal Display (LCD) provides call status and ADIX function information.

**Enhanced Security.** Super Long Range 900MHz Digital Spread Spectrum offers unparalleled range and provides superior voice communications security.

**Easy Installation.** The IX-DCKT970 plugs into an ADIX station port and provides a connection for the addition of an ADIX Omega-Phone.

### DCKT970 Features

- ▶ **Two-line, 16-digit LCD** – Displays easy-to-read information and status icons.
- ▶ **Four Programmable Keys** – Flexible keys for multiple line and feature access.
- ▶ **Headset Jack** – Hands-free operation when an optional headset is installed.
- ▶ **Memory** – Stores up to 20 phone numbers for convenient speed dialing.
- ▶ **Mute Key** – Allows users to turn off the handset microphone while on a call.
- ▶ **Vibrate Ringer Alert** – Notifies user of an incoming call by vibration versus ringing.
- ▶ **Message Waiting Display** – Illuminates when there is a message waiting.
- ▶ **10 Channels** – Supports up to 10 simultaneous calls.
- ▶ **Low Battery Protection System** – Provides six-hour talk time, four-day standby time.
- ▶ **Wall Mountable Base and Charging Unit** – Separate base unit and drop-in charge unit with convenient wall mounting

### Specifications

#### General:

Frequency Control: Phase Lock Loop  
 Modulation: Spread Spectrum  
 Operating Temperature: 0° to 50° C (+32° F to +122° F)

#### Base Unit:

Receive/Transmit Frequency: 902 MHz to 928 MHz  
 Power Requirements: 10V DC from supplied AC Adapter  
 Size: 4 1/4 in. W x 7 1/2 in. D x 2 1/4 in. H  
 Weight: Approx. 15.4 oz.  
 Color: Black

#### Handset:

Receive/Transmit Frequency: 902 MHz to 928 MHz  
 Power Requirements: Nickel-Cadmium Battery Pack  
 Size: 2 1/5 in. W x 1 2/3 in. D x 8 2/3 in. H with antenna  
 Weight: Approx. 8.8 oz. with battery  
 Battery: Capacity 800 mAh, 3.6V  
 Talk Time: 6 hours (typical)  
 Standby Time: 4 days (typical)  
 Color: Black

**IWATSU**  
 TELECOMMUNICATIONS PRODUCTS

**1-800-974-5070**  
[www.iwatsu.com](http://www.iwatsu.com)

Iwatsu America, Inc.  
 8001 Jetstar Dr.  
 Irving, TX 75063